SE-30



ORDERING DETAILS (211)



RECESSED MOUNT 0.241 Kg/Unit 30 Units/Carton



SURFACE MOUNT 0.296 Kg/Unit 30 Units/Carton

SURFACED AND RECESSED

- Ideal for use in modern hotels, commercial and public buildings, Café & Pubs etc.
- An architecturally pleasing with 2 in 1 combine accessories to enable for either recess or surface mount which inspire you and maximize the potential of your latest design concept.
- Our aim was to design a compact and easy-to-install product that would fit into an ever-diminishing ceiling void and through a minimal cut-out.
- ullet Designed , Tested and Manufactured to meet the requirements of EN 60598.2.22 & Malaysia Standard MS 619 .





















▼ TECHNICAL CHARACTERISTIC

Mode of Operation : Non-Maintained Input Voltage : 240~ VAC, 50 Hz Lamp Type : 1 x 2W LED Lamp Output : 130 lumens Input Current : 0.06A

Power Factor : 0.4

Charger : Solid State Electronic Automatic

Charger Monitor : Red LED

Test Facility : Push-To-Test Switch

Battery Type : High Temp. Sealed Nickel-Cadmium

Back Up Duration : 3 Hours
Operating Temperature : ta 35°C
Weight : 0.296 Kg
Mounting : Surface / Recess


Degree of Protection : IP 20

Fitting Construction : Injection Molded Fire Reductant Polycarbonate


Warranty : 2-5 Years (Terms & Conditions Apply)


▼ PHOTOMETRIC

Polar Luminous Intensity Distribution



DIMENSIONS





SHINZ®

Innovating Future





A NEW AGE OF

E M E R G E N C Y

ENLIGHTENMENT

SE-30